



# **EVS**Solder Recovery System

- Rapid Return On Investment –
- Months not years
- Reduces solder purchases by up to 50%
- Reduces dross off site by up to 80%
- Reduces dedrossing time by up to 85%
- <u>ISO 14001</u> EVS helps you <u>attain or retain</u> this accreditation.
- Improves wave solder machine effectiveness by reducing shorts.
- Less rework = More profit.

### LEAD FREE COMPATIBLE NOW!

# E V S IS THE LEAN - CLEAN - GREEN MACHINE

<u>LEAN</u> - Because by <u>recovering</u> up to <u>75%</u> on average pure solder by weight from solder dross, customers reduce the usage of solder in the wave soldering process by 50%.

The EVS achieves a rapid payback on its purchase price within months not years.

The **EVS** has low running costs only a single-phase socket and a standard airline.

Using **EVS** means <u>no financial penalty</u> to regular de-drossing; operators can <u>half the</u> dedrossing time returning all the solder to the pot.

<u>CLEAN</u> - Because the self-contained process avoids <u>excessive handling</u> of heavy, dirty dross, and a <u>massive reduction</u> in <u>storage</u> and <u>transportation</u>.

The **EVS** operates with an integral filtration system – filtering smells and fumes.

The **EVS** uses **NO** <u>chemicals</u>, <u>radiation</u>, <u>additives</u> or other <u>noxious substances</u>.

<u>GREEN</u> - Because the <u>EVS recovers</u> waste material <u>on site</u> at the point of manufacture <u>helping the environment</u>.

The **EVS** reduces **heavy lifting** and transportation of materials back to the supplier reducing **fuel usage** and ozone induced smog.

The **EVS** reduces paperwork, storage and administrative time and **energy**.

Because the EVS recycles on site it makes a <u>significant contribution</u> to attaining and retaining <u>ISO 14001</u>. <u>RECYCLE</u> - <u>REDUCE</u> - <u>REUSE</u>



#### E V S

So Simple You Will Hardly Believe It – So Effective You Have To.

<u>The Process</u>: <u>EVS Solder Recovery System</u> and its patented process uses heat and pressure inside a magnetised cylinder to separate and return your **pure** solder into the ingot tray. The remainder of the material is automatically ejected down a **sealed chute** into the dross bucket.

<u>The Quality Facts:</u> Hundreds of **solder assays** prove that the recovered pure solder is **exactly the same** specification as the solder in your WSM pot. This has been authenticated by the solder manufacturers and confirmed by the <u>International Tin</u> Research Council. Please look at <u>SOLDER QUALITY</u> on our website.

**Support:** EVS International supports its product through 24-hour availability of spares and service and by partnering with quality distributors who all have trained technicians and comprehensive spares stockholding.

## Turns Dross into Dollars \$ - Gives you a Rapid Return On Your Investment.

**Specification**: EVS is constructed mainly of stainless steel and cast grey iron and is controlled by integral software

with LCD service prompt.

Total System Weight 150 Kg Overall Height 1020 mm Overall Length 1200mm

**Service Requirements:** Line Power: 210/240 volts AC 50/60 Hz single phase 2.2 KVA

**Compressed Air:** 95 psi/6.5 kg/cm2 @ 3.4 cu metres per hour or 2 cu ft/min.

<u>Capacities</u>: EVS 3000 EVS 6000

Dross Input 10 Kg/22 lbs 20 Kg/44 lbs Solder Output 8 Kg/18 lbs 18 Kg/40 lbs

**Filtration:** The integral fan/filtration unit contains four separate filter medias and is effective

down to 1 micron.

**Safety Features**: Includes emergency stop, automatic over temperature cut out, fully protected

circuits, tray lock, hopper loading lock, visual light stack, air knife and CE

approval.

**Options:** One only = Extra solder ingot trays to facilitate multi wave use.

Web Site: <u>www.solderrecovery.com</u>

#### **EVS INTERNATIONAL**

Tel: +44 (0) 1983 282800 Fax: +44 (0) 1983 289652 Email: sales@evsinternational.com

Your local distributor for EVS International.